Product datasheet

Specifications

Green Premium™



M.PL.3-4V.FIXED NS250 DEVICES

03422

Discontinued on: 20 Jun 2023

Discontinued

Main

Range	Prisma
Range Of Product	Prisma P
Product Or Component Type	Mounting plate
Accessory / Separate Part Category	Installation accessory
Range Compatibility	Prisma Prisma P cubicle
Installation Description	Cubicle - width 650 mm depth 400 mm
Installed Device	EasyPact: fixed CVS100...160 without earth leakage protection - control: direct front rotary handle - vertical installation EasyPact: fixed CVS250 without earth leakage protection - control: direct front rotary handle - vertical installation ComPact: fixed NSX100...160 without earth leakage protection - control: direct front rotary handle - vertical installation ComPact: fixed NSX250 without earth leakage protection - control: direct front rotary handle - vertical installation EasyPact: fixed CVS100...160 with earth leakage protection - control: direct front rotary handle - vertical installation EasyPact: fixed CVS250 with earth leakage protection - control: direct front rotary handle - vertical installation ComPact: fixed NSX100...160 with earth leakage protection - control: direct front rotary handle - vertical installation ComPact: fixed NSX250 with earth leakage protection - control: direct front rotary handle - vertical installation ComPact: fixed NSX100...160 without earth leakage protection - control: motor mechanism - vertical installation ComPact: fixed NSX250 without earth leakage protection - control: motor mechanism - vertical installation ComPact: fixed NSX100...160 with earth leakage protection - control: motor mechanism - vertical installation ComPact: fixed NSX250 with earth leakage protection - control: motor mechanism - vertical installation
Poles Description	4 x 3P: fixed CVS100...160 vertical installation 3 x 4P: fixed CVS100...160 vertical installation 4 x 3P: fixed CVS250 vertical installation 3 x 4P: fixed CVS250 vertical installation 4 x 3P: fixed NSX100...160 vertical installation 3 x 4P: fixed NSX100...160 vertical installation 4 x 3P: fixed NSX250 vertical installation 3 x 4P: fixed NSX250 vertical installation

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Number Of Vertical Modules [50 Mm]	9 module(s): CVS100...160 without earth leakage protection , direct in 650 mm Widecubicle 9 module(s): CVS250 without earth leakage protection , direct in 650 mm Widecubicle 6 module(s): NSX100...160 without earth leakage protection , Linergy FC in 650 mm Widecubicle 8 module(s): NSX100...160 without earth leakage protection , direct in 650 mm Widecubicle 7 module(s): NSX250 without earth leakage protection , Linergy FC in 650 mm Widecubicle 9 module(s): NSX250 without earth leakage protection , direct in 650 mm Widecubicle 11 module(s): CVS100...160 with earth leakage protection , direct in 650 mm Widecubicle 11 module(s): CVS250 with earth leakage protection , direct in 650 mm Widecubicle 8 module(s): NSX100...160 with earth leakage protection , Linergy FC in 650 mm Widecubicle 10 module(s): NSX100...160 with earth leakage protection , direct in 650 mm Widecubicle 9 module(s): NSX250 with earth leakage protection , Linergy FC in 650 mm Widecubicle 11 module(s): NSX250 with earth leakage protection , direct in 650 mm Widecubicle
Standards	IEC 61439-2
Product Certifications	ASEFA

Complementary

Protective Treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Surface Finish	Matt Smooth
Colour	White
Width	606 mm
Height	147 mm
Depth	372 mm
Net Weight	2.28 kg

Functional Unit	650 mm 400 mm Prisma P cubicle EasyPact CVS100...160 without fixed direct front rotary handle vertical 3P 4 direct 9 162.5 mm 650 mm 400 mm Prisma P cubicle EasyPact CVS100...160 without fixed direct front rotary handle vertical 4P 3 direct 9 162.5 mm 650 mm 400 mm Prisma P cubicle EasyPact CVS250 without fixed direct front rotary handle vertical 3P 4 direct 9 162.5 mm 650 mm 400 mm Prisma P cubicle EasyPact CVS250 without fixed direct front rotary handle vertical 4P 3 direct 9 162.5 mm 650 mm 400 mm Prisma P cubicle ComPact NSX100...160 without fixed direct front rotary handle vertical 3P 4 Linergy FC 6 62.5 mm 650 mm 400 mm Prisma P cubicle ComPact NSX100...160 without fixed motor mechanism vertical 3P 4 Linergy FC 6 62.5 mm 650 mm 400 mm Prisma P cubicle ComPact NSX100...160 without fixed direct front rotary handle vertical 4P 3 Linergy FC 6 62.5 mm 650 mm 400 mm Prisma P cubicle ComPact NSX100...160 without fixed motor mechanism vertical 4P 3 Linergy FC 6 62.5 mm 650 mm 400 mm Prisma P cubicle ComPact NSX100...160 without fixed direct front rotary handle vertical 3P 4 direct 8 162.5 mm 650 mm 400 mm Prisma P cubicle ComPact NSX100...160 without fixed direct front rotary handle vertical 4P 3 direct 8 162.5 mm 650 mm 400 mm Prisma P cubicle ComPact NSX100...160 without fixed motor mechanism vertical 3P 4 direct 8 162.5 mm 650 mm 400 mm Prisma P cubicle ComPact NSX100...160 without fixed motor mechanism vertical 4P 3 direct 8 162.5 mm 650 mm 400 mm Prisma P cubicle ComPact NSX250 without fixed direct front rotary handle vertical 3P 4 Linergy FC 7 62.5 mm 650 mm 400 mm Prisma P cubicle ComPact NSX250 without fixed motor mechanism vertical 3P 4 Linergy FC 7 62.5 mm 650 mm 400 mm Prisma P cubicle ComPact NSX250 without fixed direct front rotary handle vertical 4P 3 Linergy FC 7 62.5 mm 650 mm 400 mm Prisma P cubicle ComPact NSX250 without fixed motor mechanism vertical 4P 3 Linergy FC 7 62.5 mm 650 mm 400 mm Prisma P cubicle ComPact NSX250 without fixed direct front rotary handle vertical 3P 4 direct 9 162.5 mm 650 mm 400 mm Prisma P cubicle ComPact NSX250 without fixed direct front rotary handle vertical 4P 3 direct 9 162.5 mm 650 mm 400 mm Prisma P cubicle ComPact NSX250 without fixed motor mechanism vertical 3P 4 direct 9 162.5 mm 650 mm 400 mm Prisma P cubicle ComPact NSX250 without fixed motor mechanism vertical 4P 3 direct 9 162.5 mm 650 mm 400 mm Prisma P cubicle ComPact NSX100...160 with fixed motor mechanism vertical 4P 3 Linergy FC 8 62.5 mm 650 mm 400 mm Prisma P cubicle ComPact NSX100...160 with fixed direct front rotary handle vertical 3P 4 direct 10 162.5 mm 650 mm 400 mm Prisma P cubicle ComPact NSX100...160 with fixed direct front rotary handle vertical 4P 3 direct 10 162.5 mm 650 mm 400 mm Prisma P cubicle ComPact NSX100...160 with fixed motor mechanism vertical 3P 4 direct 10 162.5 mm 650 mm 400 mm Prisma P cubicle ComPact NSX100...160 with fixed motor mechanism vertical 4P 3 direct 10 162.5 mm 650 mm 400 mm Prisma P cubicle ComPact NSX250 with fixed direct front rotary handle vertical 3P 4 Linergy FC 9 62.5 mm 650 mm 400 mm Prisma P cubicle ComPact NSX250 with fixed motor mechanism vertical 3P 4 Linergy FC 9 62.5 mm 650 mm 400 mm Prisma P cubicle ComPact NSX250 with fixed direct front rotary handle vertical 4P 3 Linergy FC 9 62.5 mm 650 mm 400 mm Prisma P cubicle ComPact NSX250 with fixed motor mechanism vertical 4P 3 Linergy FC 9 62.5 mm 650 mm 400 mm Prisma P cubicle ComPact NSX250 with fixed direct front rotary handle vertical 3P 4 direct 11 162.5 mm 650 mm 400 mm Prisma P cubicle ComPact NSX250 with fixed direct front rotary handle vertical 4P 3 direct 11 162.5 mm 650 mm 400 mm Prisma P cubicle ComPact NSX250 with fixed motor mechanism vertical 3P 4 direct 11 162.5 mm 650 mm 400 mm Prisma P cubicle ComPact NSX250 with fixed motor mechanism vertical 4P 3 direct 11 162.5 mm

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.0 cm
Package 1 Width	15.5 cm
Package 1 Length	58.0 cm

Package 1 Weight	2.28 kg
Unit Type Of Package 2	S04
Number Of Units In Package 2	6
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	14.6 kg
Unit Type Of Package 3	P12
Number Of Units In Package 3	72
Package 3 Height	105.0 cm
Package 3 Width	80.0 cm
Package 3 Length	120.0 cm
Package 3 Weight	175.2 kg

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Transparency RoHS/REACh

Well-being performance

Mercury Free	
Rohs Exemption Information	Yes
Halogen Free Plastic Parts Product	

Certifications & Standards

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information