


Product datasheet

Specifications



PLAIN FRONT PLATE WIDTH 600/650 6M

03806

! Discontinued on: 20 Jun 2023

! Discontinued

Main

Range	Prisma
Range Of Product	Prisma G Prisma P
Product Or Component Type	Front plate
Accessory / Separate Part Category	Installation accessory
Range Compatibility	Prisma Prisma G enclosure Prisma Prisma P cubicle
Type Of Front Plate	Plain
Installed Device	Power meters: kilowatt-hour meters - vertical installation connection Altistart: ATS01N
Poles Description	3 x 2P: mounting plate support: kilowatt-hour meters vertical installation 2 x 4P: mounting plate support: kilowatt-hour meters vertical installation

Complementary

Enclosure/Cubicle Description	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Cubicle - width 650 mm depth 400 mm Pack enclosure - width 555 mm
Number Of Vertical Modules [50 Mm]	6
Standards	IEC 61439-2 IEC 61439-1
Product Certifications	ASEFA
Material	Steel
Surface Finish	Smooth Matt
Protective Treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	White (RAL 9001)
Height	300 mm
Width	500 mm
Net Weight	1.22 kg
Quantity Per Set	Set of 1

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Functional Unit	600 mm Prisma G floor-standing enclosure power meters kilowatt-hour meters vertical 2P 3 6
	600 mm Prisma G wall-mounted enclosure power meters kilowatt-hour meters vertical 2P 3 6
	600 mm Prisma G floor-standing enclosure connection 2 6
	600 mm Prisma G wall-mounted enclosure connection 2 6
	650 mm 400 mm Prisma P cubicle connection 2 6
	600 mm Prisma G floor-standing enclosure power meters kilowatt-hour meters vertical 4P 2 6
	600 mm Prisma G wall-mounted enclosure power meters kilowatt-hour meters vertical 4P 2 6
	650 mm 400 mm Prisma P cubicle power meters kilowatt-hour meters vertical 2P 3 6
	650 mm 400 mm Prisma P cubicle power meters kilowatt-hour meters vertical 4P 2 6
	600 mm Prisma G floor-standing enclosure Altistart ATS01N 9 6
	600 mm Prisma G wall-mounted enclosure Altistart ATS01N 9 6
	600 mm Prisma G floor-standing enclosure Altistart ATS01N 2 6
	600 mm Prisma G wall-mounted enclosure Altistart ATS01N 2 6
	650 mm 400 mm Prisma P cubicle Altistart ATS01N 9 6
	650 mm 400 mm Prisma P cubicle Altistart ATS01N 2 6

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.000 cm
Package 1 Width	31.000 cm
Package 1 Length	52.000 cm
Package 1 Weight	1.250 kg
Unit Type Of Package 2	CAR
Number Of Units In Package 2	10
Package 2 Height	16.500 cm
Package 2 Width	32.400 cm
Package 2 Length	52.500 cm
Package 2 Weight	12.600 kg
Unit Type Of Package 3	P12
Number Of Units In Package 3	180
Package 3 Height	48.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	226.440 kg

Sustainability



Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency RoHS/REACH

Well-being performance

- ✓

Reach Free Of Svhc
- ✓

Toxic Heavy Metal Free
- ✓

Mercury Free
- ✓

RoHS Exemption Information

Yes
- ✓

Halogen Free Plastic Parts Product

Certifications & Standards

Eu RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile