Product datasheet

Specifications





switch-disconnector Masterpact NW10NA - 1000 A - 690 V - 4 poles - fixed

48025

Main

| Range | MasterPacT | |
|--|--|--|
| Product Name | MasterPact NW | |
| Product Or Component Type | Switch disconnector | |
| Device Short Name | MasterPact NW10 | |
| Switch-Disconnector Name | MasterPact NW10NA | |
| Device Application | Protection | |
| Poles Description | 4P | |
| Network Type | AC | |
| Network Frequency | 50/60 Hz | |
| [le] Rated Operational Current | 1000 A AC 50/60 Hz 690 V | |
| [Ui] Rated Insulation Voltage | 1000 V AC 50/60 Hz conforming to IEC 60947-3 | |
| [Uimp] Rated Impulse Withstand Voltage | 12 kV conforming to IEC 60947-3 | |
| [Icm] Rated Short-Circuit Making Capacity | 88 kA 220690 V AC at 50/60 Hz | |
| [Ue] Rated Operational Voltage | 690 V AC 50/60 Hz conforming to IEC 60947-3 | |
| Breaking Capacity Code | NA | |
| Suitability For Isolation | Yes conforming to IEC 60947-3 | |
| Contact Position Indicator | Yes | |
| Visible Break | No | |
| Pollution Degree | 4 conforming to IEC 60664-1 | |

Complementary

| Control Type | Push-button | |
|---|--|--|
| Mounting Mode | Fixed | |
| Operating Rate | 10 cyc/h maximum | |
| [Icw] Rated Short-Time Withstand Current | 42 kA during 1 s conforming to IEC 60947-3 | |
| Mechanical Durability | 12500 cycles without maintenance conforming to IEC 60947-3 25000 cycles with maintenance conforming to IEC 60947-3 | |
| Electrical Durability | AC-23A: 10000 cycles 440 V AC 50/60 Hz without maintenance conforming to IEC 60947-3 AC-23A: 10000 cycles 690 V AC 50/60 Hz without maintenance conforming to IEC 60947-3 | |
| | AC-3: 6000 cycles 440/690 V AC 50/60 Hz without maintenance conforming to IEC 60947-3 | |
| Connection Pitch | 115 mm | |

Excluding VAT, FCA Jabal Ali & are subject to change - check with your local distributor.

| Height | 352 mm |
|------------|--------|
| Width | 537 mm |
| Depth | 297 mm |
| Net Weight | 80 kg |

Environment

| Standards | IEC 60947-3 |
|--|---------------|
| Product Certifications | ASEFA ASTA |
| Ambient Air Temperature For Operation | -2570 °C |
| Ambient Air Temperature For Storage | -3585 °C |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|----------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 30.5 cm |
| Package 1 Width | 29.5 cm |
| Package 1 Length | 49.5 cm |
| Package 1 Weight | 47.27 kg |

Contractual warranty

Warranty

18 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free
Rohs Exemption Information Yes
Pvc Free

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Compliant with Exemptions |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile | End of Life Information |