Product datasheet

Specification





rectangular blue pilot light head Ø16 for integral LED

ZB6DV6

Discontinued on: 15 Jun 2023



Main

Range Of Product	Harmony XB6
Product Or Component Type	Head for pilot light
Product Compatibility	Integral LED
Device Short Name	ZB6
Bezel Material	Plastic
Mounting Diameter	16 mm
Sale Per Indivisible Quantity	1
Shape Of Signaling Unit Head	Rectangular
Cap/Operator Or Lens Colour	Blue

Complementary

Cad Overall Width	24 mm	
Cad Overall Height	18 mm	
Cad Overall Depth	33 mm	
Net Weight	0.015 kg	

Environment

Protective Treatment	TC
Ambient Air Temperature For Storage	-4070 °C
Ambient Air Temperature For Operation	-2570 °C
Electrical Shock Protection Class	Class II conforming to IEC 61140
Ip Degree Of Protection	IP65 conforming to IEC 60529
Nema Degree Of Protection	NEMA 13 conforming to UL 50 NEMA 4 conforming to UL 50 NEMA 4X conforming to UL 50 NEMA 13 conforming to CSA C22.2 No 94 NEMA 4 conforming to CSA C22.2 No 94 NEMA 4X conforming to CSA C22.2 No 94
Standards	JIS C 4520 UL 508 EN/IEC 60947-5-5 EN/IEC 60947-1 EN/IEC 60947-5-1 JIS C 852 CSA C22.2 No 14

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Product Certifications	GOST UL CSA CCC
Vibration Resistance	+/- 3 mm (f= 2500 Hz) conforming to IEC 60068-2-6 5 gn (f= 2500 Hz) conforming to IEC 60068-2-6
Shock Resistance	30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27 50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27

Packing Units

Number Of Units In Package 1 1 Package 1 Height 2.0 cm Package 1 Width 11.0 cm Package 1 Length 11.0 cm Package 1 Weight 8.0 g Unit Type Of Package 2 S01 Number Of Units In Package 2 80 Package 2 Height 15.0 cm Package 2 Width 15.0 cm Package 2 Length 40.0 cm		
Package 1 Height 2.0 cm Package 1 Width 11.0 cm Package 1 Length 11.0 cm Package 1 Weight 8.0 g Unit Type Of Package 2 S01 Number Of Units In Package 2 80 Package 2 Height 15.0 cm Package 2 Width 15.0 cm Package 2 Length 40.0 cm	Unit Type Of Package 1	PCE
Package 1 Width 11.0 cm Package 1 Length 11.0 cm Package 1 Weight 8.0 g Unit Type Of Package 2 S01 Number Of Units In Package 2 80 Package 2 Height 15.0 cm Package 2 Width 15.0 cm Package 2 Length 40.0 cm	Number Of Units In Package 1	1
Package 1 Length 11.0 cm Package 1 Weight 8.0 g Unit Type Of Package 2 S01 Number Of Units In Package 2 80 Package 2 Height 15.0 cm Package 2 Width 15.0 cm Package 2 Length 40.0 cm	Package 1 Height	2.0 cm
Package 1 Weight 8.0 g Unit Type Of Package 2 S01 Number Of Units In Package 2 80 Package 2 Height 15.0 cm Package 2 Width 15.0 cm Package 2 Length 40.0 cm	Package 1 Width	11.0 cm
Unit Type Of Package 2 S01 Number Of Units In Package 2 80 Package 2 Height 15.0 cm Package 2 Width 15.0 cm Package 2 Length 40.0 cm	Package 1 Length	11.0 cm
Number Of Units In Package 2 80 Package 2 Height 15.0 cm Package 2 Width 15.0 cm Package 2 Length 40.0 cm	Package 1 Weight	8.0 g
Package 2 Height 15.0 cm Package 2 Width 15.0 cm Package 2 Length 40.0 cm	Unit Type Of Package 2	S01
Package 2 Width 15.0 cm Package 2 Length 40.0 cm	Number Of Units In Package 2	80
Package 2 Length 40.0 cm	Package 2 Height	15.0 cm
	Package 2 Width	15.0 cm
Package 2 Weight 845.0 g	Package 2 Length	40.0 cm
	Package 2 Weight	845.0 g

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc	
②	Toxic Heavy Metal Free	
9	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards


Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

ZB6DV6

Dimensions Drawings

Rectangular Head for Pilot Light

Dimensions




Product datasheet

ZB6DV6

Mounting and Clearance


Panel Cut-out

For Rectangular Head




Pushbuttons, Switches and Pilot Lights for Printed Circuit Board Connection

Front Panel Cut-out (Viewed from Installer's Side)



Printed Circuit Board Drillings (Viewed from Electrical Block Side)



- A 24 mm/0.94 in. minimum for rectangular heads, 18 mm/0.71 in. minimum for square or circular heads
- B 18 mm/0.71 in. minimum
- (1) 6 x Ø 1.1 mm / 6 x Ø 0.04 in. holes.
- $(2) \qquad 1~x~\varnothing~2.6^{0}_{~-0.2}~mm~/~1~x~\varnothing~0.10^{0}_{~-0.008}~in.~hole~for~locating~pin,~only~when~using~socket~adaptor~ZB6Y010.$
- (3) $1 \times \emptyset \ 3.2^{0}_{-0.2} \ \text{mm} \ / \ 1 \times \emptyset \ 0.13^{0}_{-0.008}$ in. hole for fixing of printed circuit board onto the front panel using body bracket ZB6Y011. This hole must be drilled on the left-hand side, when heads are positioned at the normal angle. Fit a body bracket ZB6Y011 every 72 mm/2.83 in. maximum for cut-outs on 24 mm/0.94 in. centres (rectangular heads) and 54 mm/2.13 in. maximum for cut-outs on 18 mm/0.71 in. centres (square or circular heads).

General tolerances of the panel and printed circuit board: T1, T2: T1 + T2 = 0.3 mm/0.01 in. maximum. Installation precautions:


ZB6DV6

Thickness of printed circuit board: 1.6 mm/0.06 in. minimum.

Mounting with Body Bracket

With socket adaptor ZB6Y010






- (1) Head
- (2) Nut
- (3) Body
- (4) Body bracket
- (5) Contact block
- (6) Socket adaptor
- (7) Panel
- (8) Printed circuit

Direct mounting without socket adaptor ZB6Y010





- (1) Head
- (2) Nut
- (3) Body
- (4) Body bracket
- (5) Contact block
- (6) Panel
- (7) Printed circuit